

► ABI Mobilram

■ Mobilram VIBRATORS

Technical data	Unit	MRZV 20 VV	MRZV 22 VV	MRZV 30 VV	MRZV 36 VV
Docking-System		SKZ 1120	SKZ 1120	SKZ 1120	SKZ 1800
Static moment	kgm	0-20	0-22	0-30	0-36
Dynamic mass	kg	2820	2850	3260	3960
Nominal revolutions	min ⁻¹	2135	2035	1745	1950
Maximum revolutions	min ⁻¹	2600	2600	2600	2600
Centrifugal force at nominal frequency	kN	1000	1000	1000	1500
Maximum centrifugal force	kN	1200 ²	1200 ²	1500 ²	1500
Static extraction force max.	kN	240	240	300	300
Maximum oil pressure	MPa	35	35	35	35
Recommended installed power of carrier	kW	300 - 470	300 - 470	470 - 570	470 - 570
Total weight / transport weight	kg	4240 / 4460	4260 / 4480	4680 / 5200	5380 / 5900
Dimensions					
H	mm	3245	3245	3280	3405
B1	mm	790	790	790	790
B2 (width in piling axis)	mm	460	460	510	510
T	mm	1495	1495	1465	1465
R	mm	435	435	360	360
U	mm	870	870	910	910
S	mm	3030	3030	3065	3190
X	mm	2375	2375	2410	2410
Transport dimension	h / b t	3370 / 1040 1635	3370 / 1040 1635	3580 / 1480 1770	3630 / 1480 1770

